

# MultiPEN 4604

## RFID reader



Zone 2



This innovative MultiPEN can read LF, HF and UHF tags and transfer data via Bluetooth or USB connection to a host computer (tablet, laptop or smartphone). Thanks to its memory, the MultiPEN can even transfer information later to the host computer.

It is suitable for **ATEX Zone 2**.

It is ideal for hard-to-reach areas due to its small size and its small reading tip size.

### Key features

- RFID UHF / HF / LF
- USB / Bluetooth
- ATEX Zone 2

### Applications

- Maintenance
- Inventory
- Guard control systems
- Logistics processes

# MultIPEN 4604

## RFID reader

### General specifications

Dimensions	190mm (length) x30mm (width) x 35mm (thickness)
Weight	125g
Display Size	4 Row
Display	OLED
Battery type	Li-Ion
Battery capacity	2000 mAh
Memory	1000 UID
I/O Ports	USB
Material	Polyamid
PCB Material	FR4
Color	Black, Yellow

### Data collection

#### RFID LF, HF, UHF

Frequency Range	LF: 125-135kHz, HF: 13,56MHz, UHF: 860-920MHz
Read / Write	Read&Write
Typical Reading range	1...3 cm
Supported Standards / Tags	all

### Wireless communication

Interfaces Physical	USB / Bluetooth
Interfaces Protocol	ASCII
Transfer rate [Baud]	9600

### User environment

Compliance	RoHs & Reach, CE
Protection grade	IP54 Anticollision
Operating Temp.	-20°C to +60°C
Storage Temp.	-20°C to +60°C

### Others

Development Tools	SDK
-------------------	-----

