(((•))) AX'Label_{Classic}





AX'Label Classic 49x33 UHF



AX'Label Classic UHF line offers excellent reading performance on non-metallic equipment. They have been designed for the industrial, logistics and retail sectors.

AXEM Technology guarantees AX'Label's resistance over several years for industrial applications in indoor or outdoor environments.

AX'Label are compatible with Toshiba **BA410 printer**.

For use in an extremely harsh environment, reinforce your AX'Label with the Protect + protective film. Your AX'Label becomes AX'Label + capable of resisting water, dust, abrasion, and UV rays.


Functional specifications

RFID Protocol	EPC global and ISO 18000-63
Frequency	Global: 840 ~940 MHz
IC type	Monza 4E
Memory	EPC 496 bits, TID 96 bit Serialized , user memory 128 bits
Write Cycles	100,000 times
Functionalities	Read/write
Data Retention	50 years
Applicable Surface	Off metal

Physical specifications

Size	49 x 33mm
Material	PET soft or PET soft + coated paper
Mounting Methods	Standard adhesive or reinforced adhesive 3M467
Packaging	Reel 2500pcs

Measured read range



More about AX'Label Classic UHF range :



Item codes

ETUHF1453 ETUHF1851 AX'Label Classic UHF, Monza 4E, PET Soft, reinforced adhesive 3M467, 49x33mm AX'Label Classic UHF, Monza 4E, PET Soft, coated Paper, standard adhesive, 49x33mm

V2.0 Non-contractual datasheet