

MBA5-P21 V11



8000 mAh battery



RAM+ROM 3 GB + 32 GB /
4 GB + 64 GB (optional)



IP65
40°C ~+70°C
5% RH ~95°RH non condensing
Multiple 1.5m



RFID HF/NFC



Keyboard emulation for 2D

V1.0
Non-contractual datasheet

Physical specifications

Operating System	Android 11.0
CPU	Cortex-A53 2.3 GHz Octa-core
Memory	RAM+ROM 3 GB + 32 GB / 4 GB + 64 GB (optional)
Extended storage	Supports up to 128 GB Micro SD card
Dimensions	164.2 x 80 x 24.3mm
Display	5.2" IPS FHD 1920x1080P Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Battery	8000mAh, Li-ion, rechargeable Standby: over 500 hours Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
I/O Ports	1 Type C USB 1 slot for SIM card, 1 slot for SIM or TF card
Keys	4 front buttons, 1 side button, 2 scan keys, 1 multifunctional key
Camera	13MP Autofocus with flash
Other - general	Audio: speaker Sensors: Gravity sensor, Light Sensor, Proximity Sensor

Wireless communication

Wifi	Dual Wifi 2,4 + 5GHz IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
Bluetooth	Bluetooth 5.0
3G / 4G	3G / 4G
GPS	GPS/AGPS, GLONASS, BeiDou; internal antenna

User Environment

Operating temperature	-20°C to +50°C
Storage temperature	-40°C to +70°C
Humidity	5% – 95% relative humidity, no condensation
Protection grade	IP65 Drop Specification Multiple 1.5m/4.9ft drops (at least 20 times) to the concrete across the operating temperature range Tumble Specification 1000 x 0.5m/1.6ft falls at room temperature

V1.0

Non-contractual datasheet

Data collection

RFID

RFID High Frequency	NFC Only Frequency: 13,56MHz Protocol : ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
---------------------	---

Barcode 1D/2D (option)

1D/2D Barcode Scanner	SE4710 Option: SE4750 / SE4750MR; Honeywell: N6603 (on request)
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US, PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIK, etc).

Other module (option)

Other data capture module	Fingerprint identification: Supports fingerprint entry, image collection, fingerprint recognition, fingerprint deletion etc. Type: TCSIST Sensor type: capacitive Acquisition window size: 24.5*19mm Effective image size: 15.5*18.5mm Image size: 256*360 Resolution: 500 DPI contrast mode(1:1); search mode(1:N)
Other data capture module 2	Option Far infrared meter reading: Working frequency 37.9KHZ

Accessories



Case + anti strangulation
strap



Cradle

V1.0

Non-contractual datasheet

MBA5-P21 V11

Associated products

Item name	Base	NFC	UHF	1D/2D	Gun
MBA5-P20 V11	x	x			
MBA5-P22 V11					x
MBA5-P23 V11	x		x	x	x



MBA5-P20



MBA5 P22



MBA5 P23

V1.0

Non-contractual datasheet