

C3-2511

OEM UHF RFID antenna



C3-2511 is a **3dBi UHF RFID OEM antenna** with **circular polarization**. It is suitable for many applications: RFID logistics tracking, warehouse management, door control system...

Key features

- RFID UHF
- Gain 3 dBi
- Circular polarization
- SMA-Female connector

Applications

- RFID logistics tracking
- Warehouse management
- Door control system
- Clothing management

SMA-Femelle connector



Functional specifications

Type	UHF
Frequency	EU: 865-869MHz US: 902-928MHz
Gain	3dBi
Beam width	Hor: 110° Ver: 55°
Polarization	Circular
VSWR	≤ 1.5
F/B Ratio	≥20
Input Impedance	50 Ω
Maximum power	50W
Lightning protection	DC Ground
Antenna connector	SMA-Female

Physical specifications

Dimensions	250*110*1mm
Net weight	0.2kg
Packing size	28*12*2cm
Gross weight	0.5kg
Radome material	PCB
Radome colour	Black

Environment and industry compliance

Operating temperature	-40°C to +70°C
-----------------------	----------------

Items codes

ANTUHF1948EU	Antenne OEM C3-2511, circulaire droite, 250x110x1,5mm, 3dbi, SMA-femelle, EU
ANTUHF1948US	Antenne OEM C3-2511, circulaire droite, 250x110x1,5mm, 3dbi, SMA-femelle, US

V1.0

Non-contractual data sheet