

MBS UHF IN



5 200 mAh removable battery



RAM 4GB + ROM 64GB



IP65
-40°C ~+70°C
5% RH ~95%RH non condensing
Multiple 1.8m, 2.7m



RAIN RFID (UHF), NFC and 1D/2D barcodes included



Keyboard emulation for UHF, NFC and 2D

V1.1
Non-contractual datasheet

General specifications

Operating System	Android 13.0
CPU	Qualcomm 2.0 GHz Octa-core
Memory	RAM: 4GB + ROM: 64GB
Extended storage	Supports up to 128 GB Micro SD card
Dimensions	160 x 76 x 17mm
Weight	297g (device with battery)
Display	5.5-inch high definition (18:9), IPS LTPS 1440*720, multi-touch panel, gloves and wet hands supported
Battery	5 200 mAh removable main battery Standby: up to 490 hours (WiFi: up to 470h; 4G: up to 440h) Continuous use: over 12 hours (depending on user environment) Charging time: 2.5 hours by standard adaptor and USB cable
I/O Ports	USB3.1, Type-C, OTG
Keys	1 power key, 2 scan keys, 2 volume keys
Speaker	Support
Vibrator	Support
Microphone	2 Microphones, 1 for noise reduction
Sensors	Gravity sensor, proximity sensor, light sensor, accelerometer sensor, vibration motor
Indicator LED	Power, charging, status indicator
Card slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Camera	Rear 13MP Autofocus with flash

Wireless communication

Wifi	802.11 a/b/g/n/ac/ax-ready/d/e/h/i/k/r/v
Bluetooth	Bluetooth 5.1
3G / 4G	WWAN (Europe, Asia) : 2G: 850/900/1800/1900MHz, 3G: CDMA EVDO: BC0, WCDMA: 850/900/1900/2100MHz, TD-SCDMA: A/F(B34/B39), 4G: B1, B3, B5, B7, B8, B20, B38, B39, B40, B41 WWAN (America) : 2G: 850/900/1800/1900MHz, 3G: 850/900/1800/1900MHz, 4G: B2, B4, B5, B7, B8, B12, B13, B17, B28A, B28B, B38
GPS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna
Vo-LTE	Support Vo-LTE HD video voice call

User Environment

Operating temperature	-20°C to +50°C
Storage temperature	-40°C to +70°C
Humidity	5% RH ~95%RH non condensing
Protection grade	IP65
Drop Specification	Multiple 1.8m/5.9ft drops (at least 20 times) to the concrete across the operating temperature range Multiple 2.4m / 7.87ft. drops (at least 20 times) to the concrete after installed rubber bumper 1000 x 0.5m / 1.6ft falls at room temperature
ESD	±15KV air discharge, ±8KV conductive discharge

V1.1

Non-contractual datasheet

Data collection

RFID UHF

Engine	CM-5N module based on Impinj E510
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular polarization (-5dBi)
Power	1W (30 dBm, +5 dBm to +30 dBm adjustable)
Max. reading distance	Up to 2m depending on tag

HF/NFC

Frequency	13,56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	0-2cm

Barcode 1D/2D

1D/2D Barcode Scanner	SE4710/SE2100
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc..

Accessories



Protection case



Charging cradle

To obtain all available accessories, please contact us at commercial@axemtec.com

V1.1

Non-contractual datasheet