(((1)))AX'Label_{Classic}





AX'Label Classic 97x25

AX'Label Classic RAIN RFID (UHF) line offers excellent reading performance on non-metallic equipment. They have been designed for the industrial, logistics and retail sectors.

AXEM Technology guarantees AX'Label's resistance over several years for industrial applications in indoor or outdoor environments.

AX'Label are compatible with Toshiba **BA410 printer**.

For use in an extremely harsh environment, reinforce your AX'Label with the Protect + protective film. Your AX'Label becomes AX'Label + capable of resisting water, dust, abrasion, and UV rays.

Functional specifications

Туре	RAIN RFID (UHF)	
RFID Protocol	EPC Global Class1Gen2; ISO 18000-63/6C	
Frequency	ETSI (865-868MHz) and FCC (902-928 MHz)	
IC type	M780	
Memory	EPC: 496-bits, TID: 96-bits, User: 128-bits, Kill password: 32-bits	
Write Cycles	100,000 times	
Functionalities	Read/write, Untraceable, Lock Access	
Data Retention	50 years at 55°C	
Applicable Surface	Off metal	
Reading Distance (OFF metal)	ETSI: 18m; FCC: 14m	

Physical specifications

Size	97 x 25mm	
Material	PET soft	
Mounting Methods	Reinforced adhesive 3M467	
Packaging	Reel 2000pcs	

Environmental and industry compliance

Storage temperature	-40°C à +85°C
Operating temperature	-40°C à +85°C

Item code

ETUHF2371 AX'Label Classic UHF, M780 chip, PET, 3M 467MP adhesive, 97x25mm

V1.0

Document non contractuel